



# MONTAGE

*Sonoma*  
TILEMAKERS

COLOR PALETTE



AMALUNA - GLOSSY



AMALUNA - SILK



CHROMA - GLOSSY METALLIC



CHROMA - SILK METALLIC



CINNABAR - GLOSSY



CINNABAR - SILK



SKYLINE - GLOSSY



SKYLINE - SILK

SIZES



2 x 6



2 x 12



3 x 9



10 x 16

Montage is a handcrafted glass. A wide range of variation in color, shade and tone are to be expected within a given color.

Due to the wide color range and translucent quality, an experienced craftsman should carefully inspect, blend and install these tiles.

# MONTAGE

## SUGGESTED APPLICATIONS

### Amaluna, Cinnabar & Skyline

- Showers (including steam)
- Light Duty Floors (silk)
- Interior & Exterior areas

## SUGGESTED APPLICATIONS

### Chroma

- Interior walls including showers
- See website below for Chroma usage limitations in other areas

## KEY USAGE & INSTALLATION NOTES

- Due to the wide color range and translucent quality of Montage, an experienced craftsman must carefully inspect, blend and install these tiles.
- Verify color acceptability of tiles prior to installation. Montage tiles should be inspected and compared to one another on a white background. Blend the entire order prior to installation to ensure a visually consistent installation.
- The color of thin-set will affect the installed tile appearance. Confirm the thin-set color chosen is acceptable prior to installation.
- Chroma glass requires specific installation materials. See website noted below for further information.
- For cutting, use a high quality wet tile saw with a continuous, smooth-rim diamond blade made for cutting glass tile. Always cut slowly.

➤ See **STM Tech Info** at [sonomatilemakers.com](http://sonomatilemakers.com) for more detailed information.

## INSPECTION AND INSTALLATION

Always inspect your tiles before they are installed, as installation of material constitutes acceptance. Any questions as to acceptability must be resolved before installation. We are in no way responsible for the installation of our tiles or thereafter. The responsibility for correct installation rests with the end user.

## ASTM RESULTS

TEST #	TYPE OF TEST	GLOSSY	SILK
C650	Chemical Resistance	No affect	No affect
C1028	Static Coefficient	Dry .73 / Wet .45	Dry .76 / Wet .63
ISO 10545-4	Breaking Strength	> 1500 N	> 1500 N
	Modulus of Rupture	> 35 N/mm <sup>2</sup>	> 35 N/mm <sup>2</sup>
A137.2	Thermal Shock	No affect	No affect



## GLOBAL PRODUCTS

As purveyors of fine tile, our expectations of quality and integrity are extended to ALL products that we carry.

When a product cannot be produced in California, we carefully select and work with factories around the world to produce the best ceramic, glass and stone for our customer's needs.

## HANDCRAFTED CHARACTERISTICS

Montage is a handcrafted glass. A wide range of variation in color, shade and tone are to be expected within a given color. Due to the color range and translucent quality, an experienced craftsman should carefully inspect, blend and install these tiles. The tiles finally purchased will vary from both the catalog illustrations and samples. See Tech Info at [sonomatilemakers.com](http://sonomatilemakers.com) for further information on application and installation guidelines for Montage.

Cover Photo: 2x6 shown in Skyline - Glossy